

Full Professional Performance and Features in a Small Form Factor.

The Quadro P1000 combines a 640 CUDA core Pascal GPU, 4 GB GDDR5 on-board memory and advanced display technologies in a low-profile form factor to deliver amazing graphics performance for demanding professional applications. Support for four 4K displays (4096x2160 @ 60Hz) with HDR color gives you an expansive visual workspace to see your ideas come to life in stunning detail.

Quadro cards are certified with a broad range of sophisticated professional applications, tested by leading workstation manufacturers, and backed by a global team of support specialists. This gives you the peace of mind to focus on doing your best work. Whether you're developing revolutionary products or telling spectacularly vivid visual stories, Quadro gives you the performance to do it brilliantly.

THE PNY ADVANTAGE

PNY provides unsurpassed service and commitment to its professional graphics customers. In addition, PNY delivers a complete solution that includes the appropriate adapters, cables, brackets, driver software installation disc, and documentation to ensure a quick and successful install.

FEATURES

- > Four mini DisplayPort 1.4 Connectors¹
- > DisplayPort with Audio
- » NVIDIA nView® Desktop Management Software
- > HDCP 2.2 Support
- > NVIDIA Mosaic²
- > NVIDIA Iray and MentalRay Support

PACKAGE CONTENTS

- > NVIDIA® Quadro® P1000 Professional Graphics Board
- > Aattached full-height (ATX) bracket
- > Unattached low-profile (SFF) bracket
- > Four mDP to DP adapters
- > Printed Quick Start Guide
- > Printed Support Guide

WARRANTY AND SUPPORT

- > 3-Year Warranty
- > Pre- and Post-Sales Technical Support
- > Dedicated Field Application Engineers
- > Direct Tech Support Hot Lines



| PNY PART NUMBER | VCQP1000V2-PB |
|------------------------------|--------------------------------------------------------------------|
| SPECIFICATIONS | |
| GPU Memory | 4 GB GDDR5 |
| Memory Interface | 128-bit |
| Memory Bandwidth | Up to 80 GB/s |
| NVIDIA CUDA® Cores | 640 |
| System Interface | PCI Express 3.0 x16 |
| Max Power Consumption | 47 W |
| Thermal Solution | Active |
| Form Factor | 2.713" H x 6.061" L, Single Slot, Low Profile |
| Display Connectors | 4x mDP 1.4 |
| Max Simultaneous Displays | 4 direct, 4 DP 1.4 Multi-Stream |
| Display Resolution | 4x 4096x2160 @ 60Hz 4x 5120x2880 @ 60Hz |
| Graphics APIs | Shader Model 5.1, OpenGL 4.5³, DirectX 12.0⁴, Vulkan 1.0³ |
| Compute APIs | CUDA, DirectCompute, OpenCL™ |
| | |

© 2021 NVIDIA Corporation and PNY. All rights reserved. NVIDIA, the NVIDIA logo, Quadro, nView, CUDA, and NVIDIA Pascal are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. The PNY logotype is a registered trademark of PNY Technologies. OpenCL is a trademark of Apple Inc. used under license to the Khronos Group Inc. All other trademarks and copyrights are the property of their respective owners. JUN21





¹ VGA/DVI/HDMI support via adapter/connector/bracket | ² Windows 7, 8, 8.1 and Linux | ³ Product is based on a published Khronos Specification, and is expected to pass the Khronos Conformance lesting Process when available. Current conformance status can be found at www.khronos.org/conformance | ⁴ GPU supports DX 12.0 API, Hardware Feature Level 12_1